

Specification

Main Board CPU Socket LGA1155 for Intel Core i7/i5/i3/Celeron (Ivy Bridge and Sandy Bridge Memory 2 x DDR3 SO-DIMM Socket up to 16GB Memory 2 x DDR3 SO-DIMM Socket up to 16GB Chipset Intel® Q77 Chipset Graphics Integrated Intel® HD Graphics built-in Visuals Network 2 x RJ-45 w/ LED GbE LAN1:Intel® 82583V, LAN2: Intel® 82579LM Audio HD audio Power Supply 220W ATX power supply OS Windows 8.1 Professional 32 / 64bits Windows 7 Professional 32 / 64bits Windows 7 Standard Speaker 2 x 2W speaker Printer Thermal Printer 3" receipt printer w/paper near end sensor, 180mm/sec Display LCD 19" 4:3 LCD Panel Resolution 1920 x 1080 Brightness 350nits Touch Screen IR touch solution Storage HDD 1 x 3.5" SATA HDD Payment System	
CPU Socket LGA1155 for Intel Core i7/i5/i3/Celeron (Ivy Bridge and Sandy Bridge Memory 2 x DDR3 SO-DIMM Socket up to 16GB Chipset Intel® Q77 Chipset Graphics Integrated Intel® HD Graphics built-in Visuals Network 2 x RJ-45 w/ LED GbE LAN1:Intel® 82583V, LAN2: Intel® 82579LM Audio HD audio Power Supply 220W ATX power supply OS Windows 8.1 Professional 32 / 64bits Windows 7 Professional 32 / 64bits Windows 7 Standard Speaker 2 x 2W speaker Printer Thermal Printer 3" receipt printer w/paper near end sensor, 180mm/sec Display LCD 19" 4:3 LCD Panel Resolution 1920 x 1080 Brightness 350nits Touch Screen IR touch solution Storage HDD 1 x 3.5" SATA HDD	
Memory2 x DDR3 SO-DIMM Socket up to 16GBChipsetIntel® Q77 ChipsetGraphicsIntegrated Intel® HD Graphics built-in VisualsNetwork2 x RJ-45 w/ LED GbE LAN1:Intel® 82583V, LAN2: Intel® 82579LMAudioHD audioPower Supply220W ATX power supplyOSWindows 8.1 Professional 32 / 64bits Windows 7 Professional 32 / 64bits Windows 7 StandardSpeaker2 x 2W speakerPrinter3" receipt printer w/paper near end sensor, 180mm/secDisplayLCDLCD19" 4:3 LCD PanelResolution1920 x 1080Brightness350nitsTouch ScreenIR touch solutionStorageHDDHDD1 x 3.5" SATA HDD	
ChipsetIntel® Q77 ChipsetGraphicsIntegrated Intel® HD Graphics built-in VisualsNetwork2 x RJ-45 w/ LED GbE LAN1:Intel® 82583V, LAN2: Intel® 82579LMAudioHD audioPower Supply220W ATX power supplyOSWindows 8.1 Professional 32 / 64bits Windows 7 Professional 32 / 64bits Windows 7 StandardSpeaker2 x 2W speakerPrinter3" receipt printer w/paper near end sensor, 180mm/secDisplayLCD19" 4:3 LCD PanelResolution1920 x 1080Brightness350nitsTouch ScreenIR touch solutionStorageHDD1 x 3.5" SATA HDD	
GraphicsIntegrated Intel® HD Graphics built-in VisualsNetwork2 x RJ-45 w/ LED GbE LAN1:Intel® 82583V, LAN2: Intel® 82579LMAudioHD audioPower Supply220W ATX power supplyOSWindows 8.1 Professional 32 / 64bits Windows 7 Professional 32 / 64bits Windows 7 StandardSpeaker2 x 2W speakerPrinter3" receipt printer w/paper near end sensor, 180mm/secDisplayLCDLCD19" 4:3 LCD PanelResolution1920 x 1080Brightness350nitsTouch ScreenIR touch solutionStorageHDDHDD1 x 3.5" SATA HDD	
Network2 x RJ-45 w/ LED GbE LAN1:Intel® 82583V, LAN2: Intel® 82579LMAudioHD audioPower Supply220W ATX power supplyOSWindows 8.1 Professional 32 / 64bits Windows 7 Professional 32 / 64bits Windows 7 StandardSpeaker2 x 2W speakerPrinterThermal PrinterThermal Printer3" receipt printer w/paper near end sensor, 180mm/secDisplayLCD19" 4:3 LCD PanelResolution1920 x 1080Brightness350nitsTouch ScreenIR touch solutionStorageHDD1 x 3.5" SATA HDD	
AudioHD audioPower Supply220W ATX power supplyOSWindows 8.1 Professional 32 / 64bits Windows 7 Professional 32 / 64bits Windows 7 StandardSpeaker2 x 2W speakerPrinterThermal Printer3" receipt printer w/paper near end sensor, 180mm/secDisplayLCD19" 4:3 LCD PanelResolution1920 x 1080Brightness350nitsTouch ScreenIR touch solutionStorageHDD1 x 3.5" SATA HDD	
Power Supply 220W ATX power supply Windows 8.1 Professional 32 / 64bits Windows 7 Professional 32 / 64bits Windows 7 Standard Speaker Printer Thermal Printer 3" receipt printer w/paper near end sensor, 180mm/sec Display LCD 19" 4:3 LCD Panel Resolution 1920 x 1080 Brightness 350nits Touch Screen IR touch solution Storage HDD 1 x 3.5" SATA HDD	
OS Windows 8.1 Professional 32 / 64bits Windows 7 Professional 32 / 64bits Windows 7 Standard Speaker 2 x 2W speaker Printer Thermal Printer 3" receipt printer w/paper near end sensor, 180mm/sec Display LCD 19" 4:3 LCD Panel Resolution 1920 x 1080 Brightness 350nits Touch Screen IR touch solution Storage HDD 1 x 3.5" SATA HDD	
Windows 7 Professional 32 / 64bits Windows 7 Standard Speaker 2 x 2W speaker Printer Thermal Printer 3" receipt printer w/paper near end sensor, 180mm/sec Display LCD 19" 4:3 LCD Panel Resolution 1920 x 1080 Brightness 350nits Touch Screen IR touch solution Storage HDD 1 x 3.5" SATA HDD	
Windows 7 Standard Speaker 2 x 2W speaker Printer Thermal Printer 3" receipt printer w/paper near end sensor, 180mm/sec Display LCD 19" 4:3 LCD Panel Resolution 1920 x 1080 Brightness 350nits Touch Screen IR touch solution Storage HDD 1 x 3.5" SATA HDD	
Speaker2 x 2W speakerPrinter3" receipt printer w/paper near end sensor, 180mm/secDisplay19" 4:3 LCD PanelResolution1920 x 1080Brightness350nitsTouch ScreenIR touch solutionStorageHDD1 x 3.5" SATA HDD	
Printer Thermal Printer 3" receipt printer w/paper near end sensor, 180mm/sec Display LCD 19" 4:3 LCD Panel Resolution 1920 x 1080 Brightness 350nits Touch Screen IR touch solution Storage HDD 1 x 3.5" SATA HDD	
Thermal Printer 3" receipt printer w/paper near end sensor, 180mm/sec Display LCD 19" 4:3 LCD Panel Resolution 1920 x 1080 Brightness 350nits Touch Screen IR touch solution Storage HDD 1 x 3.5" SATA HDD	
Display LCD 19" 4:3 LCD Panel Resolution 1920 x 1080 Brightness 350nits Touch Screen IR touch solution Storage HDD 1 x 3.5" SATA HDD	
LCD19" 4:3 LCD PanelResolution1920 x 1080Brightness350nitsTouch ScreenIR touch solutionStorageHDDHDD1 x 3.5" SATA HDD	
Brightness 350nits Touch Screen IR touch solution Storage HDD 1 x 3.5" SATA HDD	
Touch Screen IR touch solution Storage HDD 1 x 3.5" SATA HDD	
Touch Screen IR touch solution Storage HDD 1 x 3.5" SATA HDD	
HDD 1 x 3.5" SATA HDD	
Payment System	
Bill Validator Option	
Coin Acceptor Option	
IC Card Option	
eMoney Option	
External I/O Ports	
USB Ports 4 x USB3.0, 2 x USB2.0	
Serial Ports 2 x RS232	
LAN 2 x RJ45 (LAN2 reserved for payment system connection)	
PS/2 1 (Combo)	
Audio 2 (Mic-in, Line-out)	
VGA 1 x D-SUB 15pin	
HDMI	
Physical dimensions	
Weight JTK-1900 W/ Payment System: 88kgs	
JTK-1900 W/O Payment System: 72kgs	
Environment	
EMC & Safety 500mm (W) x 1513mm (L) x 351mm (D)	
Temperature Operating: 0° ~40°C; Storage: -20° ~80°C	
Humidity 20% ~80%	





